



CONCRETE BLOCK OR BRICK AT OPTION OF THE ENGINEER. IF BRICK OR BLOCK APPLY 1/2" COAT 1:2 CEMENT MORTAR INSIDE & OUT.

CONCRETE BLOCK, ASTM DESIGNATION C-189 (COMMON). ASTM DESIGNATION C-62 GRADE, SWM.

NOTES:
 1. VERIFY EXISTING CONDITIONS AND ELEVATIONS AT THE SITE BEFORE STARTING WORK.
 2. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AT THE SITE BEFORE STARTING WORK.
 3. ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 4. ALL WORK SHALL BE IN ACCORDANCE WITH THE LATEST EDITIONS OF THE STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, N.Y.S.D.O.T. 1999.

GENERAL SITE - CONSTRUCTION DETAILS
 100 UNITS LOW RENT HOUSING
 P.H.A. N.Y. 11-2 FOR THE
 NIAGARA FALLS HOUSING AUTHORITY
 NIAGARA FALLS, N.Y.
 SHACKLETON and FITZGERALD, A.I.A.
 ARCHITECTS
 119 LOCKPORT STREET
 NIAGARA FALLS, N.Y.
 DATE 5-15-00
 DWG. NO. S-6